

IN_RING TUB S A 60

Code	09.0361.7.930.BK
Color	Black
Input Wattage	5.4 W
Luminaire luminous flux	570 Lm
Luminaire efficacy	105.6 lm/W
CCT	3000K
CRI	>90
Voltage (V)	48V
Warranty	5 Years
IP Grade	IP20

OPTICAL

Type	CREE LED
Light beam angle	50°
Light distribution	Symmetric

ELECTRICAL


Driver	Included
Power factor	0.8
LED input Voltage (nominal)	9V
LED input Current (nominal)	600mA
Dimming	NO DIM
Electrical insulation class	Class III

OTHER DATA


Track type	IN_RING TRACK 48V DC
Swivel angle	90°
Rotation angle	355°
Materials	Aluminium / Polycarbonate
Weight	0.112 kg
Gross weight	0.134 kg



DIMENSIONS



ACCESSORY




CERTIFICATIONS




TUB S ACCESSORY

Model HONEYCOMB TUB S
Category Accessories



Code 06.A03HC
Color Black




TUB S ACCESSORY


Model LENS TUB S
Category Accessories




Code 06.A03LS24
Light beam angle 24°
Color Transparent



Code 06.A03LS32
Light beam angle 32°
Color Transparent





**IN_RING 48V**

	Code	Dimensions (mm): LxWxH	Color
IN_RING 200 48V 2m with 3 parts*	06.C200.BK	2000 x 30 x 54	White
IN_RING 300 48V 2m with 3 parts*	06.C200.BK	2000 x 30 x 54	Black
IN_RING 500 48V 3m with 6 parts*	06.C300.WH	3000 x 30 x 54	White
IN_RING 200 48V 3m with 6 parts*	06.C300.BK	3000 x 30 x 54	Black
IN_RING 300 48V 5m with 8 parts*	06.C500.WH	5000 x 30 x 54	White
IN_RING 500 48V 5m with 8 parts*	06.C500.BK	5000 x 30 x 54	Black


*See mounting instructions

ALL 48V TRACK IN_RING**IN_RING LIVE END 600**

	Code	Dimensions (mm): LxWxH	Color
Feed cable	06.CLE60.WH	600	White
	06.CLE60.BK	600	Black


**IN_RING ELECTRICAL JOINT FLEX**

	Code	Color
Electrical joint flex connector for tack	06.C2LE60.WH	White
	06.C2LE60.BK	Black

**CERTIFICATIONS**

ALL 48V TRACK IN_RING

POWER SUPPLY




Code	Dimensions (mm): LxWxH	Power Watt	Color
PS-60-48	162,5 x 42,5 x 32	60	Grey
PS-100-48	190 x 52 x 37	100	Grey
PS-150-48	191 x 63 x 37,5	150	Grey

CE IP67 48V

DRIVER MUST BE PLACED ON REMOTE

POWER SUPPLY



Code	Dimensions (mm): LxWxH	Power Watt	Color
06.PSU.100.W/O	298 x 30 x 16,5	100	Grey
06.PSU.200.W/O	384 x 30 x 22	200	Grey
06.PSU.250.W/O	384 x 30 x 22	250	Grey

CE IP20 48V

DRIVER MUST BE PLACED ON REMOTE

CERTIFICATIONS

